



Structerm
STRUCTURAL INSULATED FACADES

**Anthracite
Smooth**

Anthracite Smooth

From the  **Feldhaus Klinker**
WIR GEHÖREN ZUM GUTEN TON. range.

Manufactured to DIN EN 771-1
and DIN 105-100

Type

Extruded Clay Brick Slips

Standard work size

215 x 20 x 65mm

Dimensional tolerances

Tolerance category: T1

Range category: R1

Compressive strength

15N/mm²

Water absorption

≤ 6%

Durability

F2

Active soluble salts content

S2

Reaction to Fire

A1

Dry weight per slip

0.45kg

Pack sizes

24 per box / 96 boxes per pallet

Part Number

DBA700



Structherm
STRUCTURAL INSULATED FACADES

Structherm Ltd

Bent Ley Road

Meltham

Holmfirth

West Yorkshire

HD9 4AP

t: 01484 850098

f: 01484 851388

e: info@structherm.co.uk

www.structherm.co.uk

 **Feldhaus Klinker**

WIR GEHÖREN ZUM GUTEN TON.

DISCLAIMER:

The reproduction of colours and textures is only as accurate as the printing process will allow. Photographic samples should be used when shortlisting products but we advise that an actual sample should be seen before ordering.