

Product Data Sheet – Structherm Standard Basecoat

Structherm Standard Basecoat is a high quality all purpose sprayable base coat with excellent workability qualities, designed to be used over block work as a primary coat for Structherm finishes and is ideal as the background for thin coat acrylic finishes.

All Structherm base coats are polymer modified and cement based to ensure flexibility and strength. Scratch coats require only the addition of water and 5 minutes mixing time. Normally applied in one coat as a backing for Structherm finishes. Rule off to a flat finish and scratch lightly to provide a key for the next coat.


COVERAGE

1.8kg/ mm thick/ sqm

REQUIRE

14-18kg/sq m approx.
nominal 8-10mm thickness

In some cases, the incorporation of Structherm scrim cloth reinforcement is advised. For work on unusual substrates always seek technical advice.

KITEMARK CLASSIFICATIONS TM
Compressive strength: CS IV
Capillary Water Absorption Category: W2
Thermal Conductivity: P=50% - 0.43

SUPPORT BACKINGS

Structherm Standard Basecoat can be used over block work masonry or stone backgrounds. For Insulation, concrete, refurbishment work or any other unusual substrate seek technical advice

APPLICATION

- Mix for at least 5 minutes to break down additives
 - Add 5-6 Litres of clean water per 25kg sack
 - Can be spray machine applied
-