

EJOT® self-drilling fasteners

TS 6.3 x L range



Case hardened steel fastener for fixing roofing or cladding steel sheets to timber.

Application Features

- Mechanical performance is dependent on embedment and grade of timber
- Can be used in conjunction with A15 and A19 aluminium/EPDM vulcanised sealing washers
- 8mm AF hexagon drive

Material Specification

- High quality case hardened low carbon steel manufactured in accordance with BS EN ISO 10666
- Organic corrosion resistant finish



Drive Tool



Self-drilling fastener range

Performance Details

Ultimate Fastener Tensile Strength

Fastener Diameter	kN
6.3 x L	16.10

Ultimate Fastener Shear Strength

Fastener Diameter	kN
6.3 x L	10.70

Ultimate Pullout Load kN

Fastener Diameter	Nominal Steel Thickness (mm)		
	25	32	45
6.3 x L	2.10	2.40	3.70

Figures based on tests from construction grade timber.

Ultimate Pullover Load kN

Washer Face	Nominal Steel Thickness (mm)			
	0.50	0.70	0.90	1.20
A15 Washer	3.52	4.62	5.72	-
A19 Washer	3.74	5.33	6.91	9.28

Figures based on use with R38 profile steel sheets with fastener located in valley of profile.

Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.